

## AMENDMENTS

### In the Claims:

This listing of claims replaces all prior versions, and listings, of claims in the application:

1. (Currently Amended) A semiconductor light-emitting device, comprising:

a lead frame having a main surface in which a first region and a second region extending along a periphery of said first region are defined;

a semiconductor light-emitting element provided at said first region;

a first resin member having a first reflectivity with respect to light emitted from said semiconductor light-emitting element and provided at said first region to completely cover said semiconductor light-emitting element; and

a second resin member having a second reflectivity greater than said first reflectivity with respect to the light emitted from said semiconductor light-emitting element and provided at said second region to surround said semiconductor light-emitting element;

wherein said first resin member includes a first top surface,

said second resin member is formed of a polyamide-based resin,

said second resin member includes a second top surface that is provided at a position where a distance from said main surface is greater than a distance from said main surface to said first top surface, and an inner wall that is provided on a side where said semiconductor light-emitting element is located and extends in a direction away from said main surface to reach said second top surface,

said inner wall provides a reflecting surface for reflecting light emitted from said first top surface at the position where the distance from said main surface is greater than the distance from said main surface to said first top surface, and

said inner wall is exposed from said first resin member at the position where the distance from said main surface is greater than the distance from said main surface to said first top surface.

2. (Previously Presented) The semiconductor light-emitting device according to claim 1, further comprising a metallic wire having one end connected to said semiconductor light-emitting element and another end connected to said main surface, and said first resin member is provided to completely cover said metallic wire.

3. (Previously Presented) The semiconductor light-emitting device according to claim 2, wherein said one end is formed in a line shape, and said another end is formed in a ball shape.

4. (Previously Presented) The semiconductor light-emitting device according to claim 2, wherein said one end is provided with a ball-shaped metal to sandwich said metallic wire between the ball-shaped metal and said semiconductor light-emitting element.

5-6. (Cancelled)

7. (Currently Amended) A semiconductor light-emitting device, comprising:  
a lead frame having a main surface in which a first region and a second region extending along the periphery of said first region are defined;

a semiconductor light-emitting element provided at said first region;

a first resin member having a first reflectivity with respect to light emitted from said semiconductor light-emitting element and provided at said first region to completely cover said semiconductor light-emitting element; and

a second resin member having a second reflectivity greater than said first reflectivity with respect to the light emitted from said semiconductor light-emitting element and provided at said second region to surround said semiconductor light-emitting element, wherein

said first resin member includes a first top surface,

said second resin member includes a second top surface that is provided at a position where a distance from said main surface is greater than a distance from said main surface to said first top surface, and an inner wall that is provided on a side where said semiconductor light-emitting element is located and extends in a direction away from said main surface to reach said second top surface,

said inner wall is exposed from said first resin member at the position where the distance from said main surface is greater than the distance from said main surface to said first top surface, and

said lead frame is unfolded and in a plate shape that extends in one plane, said lead frame includes terminal portions separated from each other by a slit-shaped groove, and said portions are formed thinner than the other portion of said lead frame.

8. (Previously Presented) The semiconductor light-emitting device according to claim 1, wherein said lead frame is formed in a plate shape extending in one plane.

9. (Previously Presented) The semiconductor light-emitting device according to claim 8, wherein said lead frame includes a first depression that is formed at an opposite surface with respect to said main surface and filled with a resin, and terminal portions to be electrically connected to a mounting board are provided on said opposite surface, on respective sides of said first depression.

10. (Previously Presented) The semiconductor light-emitting device according to claim 1, wherein said lead frame includes a second depression formed at said first region, and said semiconductor light-emitting element is provided in said second depression.

11. (Previously Presented) The semiconductor light-emitting device according to claim 1, wherein said lead frame is formed of a metal having a heat conductivity of not lower than 300 W/mK and not greater than 400 W/mK.

12. (Previously Presented) The semiconductor light-emitting device according to claim 1, wherein said second resin member is formed such that an area of a shape defined by said inner wall in a plane parallel to said main surface increases with an increase of a distance from said main surface.

13. (Previously Presented) The semiconductor light-emitting device according to claim 1, wherein a shape defined by said inner wall in a plane parallel to said main surface is one of circle, ellipse and polygon.

14-17. (Canceled)

18. (Previously Presented) An electronic image pickup device, comprising the semiconductor light-emitting device recited in claim 1.

19. (Previously Presented) The electronic image pickup device according to claim 18, wherein when a reference plane of a rectangular shape is provided at a prescribed distance from said semiconductor light-emitting device, luminance at each corner of said reference plane irradiated with the light from said semiconductor light-emitting device is not less than 50% of luminance at the center of said reference plane.

20. (Previously Presented) A semiconductor light-emitting device, comprising:  
three lead frames spaced apart and extending in different directions from each other, each lead frame comprising

a main surface in which a first region and a second region extending along the periphery of said first region are defined;

a semiconductor light-emitting element provided at said first region;

a first resin member having a first reflectivity with respect to light emitted from said semiconductor light-emitting element and provided at said first region to completely cover said semiconductor light-emitting element;

a second resin member having a second reflectivity greater than said first reflectivity with respect to the light emitted from said semiconductor light-emitting element and provided at said second region to surround said semiconductor light-emitting element; wherein

said first resin member includes a first top surface,

said second resin member includes a second top surface that is provided at a position where a distance from said main surface is greater than a distance from said main surface to said first top surface, and an inner wall that is provided on a side where said semiconductor light-emitting element is located and extends in a direction away from said main surface to reach said second top surface, and

said light-emitting elements are for emitting light of a different color, each color selected from the group of red, blue, and green.

21. (Previously Presented) The semiconductor light-emitting device according to claim 20, wherein areas of said main surfaces of said lead frames provided with said semiconductor light-emitting elements for emitting the light of blue and green, respectively, are each greater than an area of said main surface of said lead frame provided with said semiconductor light-emitting element emitting the light of red.

22. (Previously Presented) The semiconductor light emitting device according to claim 1, wherein a surface of said inner wall is plated.